



Small and powerful energy saver gives high quality light, with compact design

GENIE

Functional non-covered Energy saving lamp, with money saving high quality light and compact design. This lamp is small enough to fit neatly wherever you need extra bright light at home, enables easy replacement of most incandescent lamp all the way.

Benefícios

- Compact energy saving lamp enables fitting neatly wherever extra brightness is needed
- Save your money with long life-time and high energy efficiency compare to incandescent lamp
- Flicker-free start & Fast run up

Características

- Long-Life and Energy saving alternative to Incandescent lamps
- Fast run-up
- Recommended ambient temperature range to ensure almost constant light output (>90%): between 0 and +50° C

Aplicação

- Designed for incandescent lamp replacement in consumer applications where the lamp is not directly visible, especially suitable for indoor applications in functional areas.
- Enclosed fixtures required for outdoor applications
- Not suitable for use with dimmers or electronic gear

Avisos e Segurança



- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Versions



LPPR ECONCFLG 0033

Desenho dimensional



Product

GENIE 11W CDL E14 220-240V 1PF/6

Product	D (max)	C (max)	F (max)
GENIE 11W CDL E14 220-240V 1PF/6	35,0 mm	120 mm	44,5 mm

Desenho dimensional



Product	D (max)	C (max)	F (max)
GENIE 8W CDL E27 220-240V 1PF/6	36 mm	108 mm	44,5 mm

Dados técnicos de luminosidade

Coordenada de cromaticidade X (Nom)	313
Coordenada de cromaticidade Y (Nom)	337
Designação da cor	Luz natural fria
Temperatura de cor correlacionada	6500 K
LLMF no final da vida útil nominal (Nom.)	65 %

Dados elétricos e de funcionamento

Frequência de entrada	50 ou 60 Hz
Tensão (Nom.)	220-240 V
Tempo de arranque (Nom.)	0,3 s

Controles e regulação

Intensidade regulável	Não
-----------------------	-----

Dados mecânicos e de revestimento

Forma da lâmpada	Linear
------------------	--------

Aprovação e aplicação

Conteúdo de mercúrio (Hg) (Máx.)	2 mg
Conteúdo de mercúrio (Hg) (Nom.)	1,5 mg

Informações gerais

Order Code	Full Product Name	Casquilho-Base
80228610	GENIE 8W CDL E27 220-240V 1PF/6	E27
80257610	GENIE 11W CDL E14 220-240V 1PF/6	E14

Dados técnicos de luminosidade

Order Code	Full Product Name	Eficiência Luminosa (nominal) (Nom)
80228610	GENIE 8W CDL E27 220-240V 1PF/6	50 lm/W

Order Code	Full Product Name	Eficiência Luminosa (nominal) (Nom)
80257610	GENIE 11W CDL E14 220-240V 1PF/6	52 lm/W

Dados elétricos e de funcionamento

Order Code	Full Product Name	Corrente de lâmpada (Nom.)
80228610	GENIE 8W CDL E27 220-240V 1PF/6	60 mA

Order Code	Full Product Name	Corrente de lâmpada (Nom.)
80257610	GENIE 11W CDL E14 220-240V 1PF/6	80 mA

Aprovação e aplicação

Order Code	Full Product Name	Consumo de energia kWh/1000 h
80228610	GENIE 8W CDL E27 220-240V 1PF/6	8 kWh

Order Code	Full Product Name	Consumo de energia kWh/1000 h
80257610	GENIE 11W CDL E14 220-240V 1PF/6	11 kWh

